COMPONENT PREPARATION

BURST & ZICK C043 BV

Cutting, embossing and bending machine for taped axial components with heavier leads, vertical form

Vertical form | Leads over 0.8–1.3 mm | Up to 5,000 pcs/h | Pitch 2.5–7.5 mm



OVERVIEW

The C043 BV is the vertical-form version for heavier leads, over 0.8 mm up to 1.3 mm, and a pitch up to 7.5 mm. Axially taped components are cut, bent and, if needed, embossed into standing components.

Cut length and pitch are set with adjusting spindles; embossing tools are made to the customer's requirement. Taped components are processed automatically at an infinitely variable speed; a tool change takes about 5 minutes.

TECHNICAL SPECIFICATIONS

Forms	Vertical
Pitch	2.5–7.5 mm
Lead diameter	Over 0.8 to 1.3 mm
Components	Taped
Output	Max. 5,000 pcs/h (infinitely variable)
Power	230 V / 50 Hz / 140 W
Dimensions	840 (with reel holder) × 480 × 450 mm
Weight	Approx. 55 kg
Options	Preset and piece counter, holder for reel or ammo pack

Configuration, demo and quotation

InterElectronic supplies this machine in Hungary and Central Europe: application advice, sample tests, installation, training and service.

InterElectronic Hungary, H-2461 Tárnok, Pacsírtamező street 3 D/1

Phone +36 30 296 45 05

Email info@interelectronic.com

Web www.interelectronic.com

Specifications according to Burst & Zick. Subject to change without notice.