COMPONENT PREPARATION

BURST & ZICK C095

PLC-controlled cutting machine for radial taped components

Siemens S7-1200 | Tape 12.7 / 15 mm | Max. 5,000 pcs/h | Reel or ammo pack



OVERVIEW

The C095 was developed for the efficient cutting of radial taped components. The components are fed from reels only, with a combined holder for reel or ammo pack.

Easily exchanged tape guides and tools allow both 12.7 mm and 15 mm tape hole pitch. The cut components are collected as bulk in a container.

TECHNICAL SPECIFICATIONS

Control	Siemens S7-1200
Pitch	2.5–10 mm
Tape hole pitch	12.7 and 15 mm
Lead diameter	0.4–0.8 mm
Feeding	Reel or ammo pack
Delivery	Bulk
Output	Max. 5,000 pcs/h
Power	230 V / 50 Hz
Compressed air	6 bar
Dimensions	500 × 400 × 450 mm
Weight	Approx. 20 kg

Configuration, demo and quotation

InterElectronic supplies this machine in Hungary and Central Europe: application advice, sample tests, installation, training and service.

InterElectronic Hungary, H-2461 Tárnok, Pacsírtamező street 3 D/1

Phone +36 30 296 45 05

Email info@interelectronic.com

Web www.interelectronic.com

Specifications according to Burst & Zick. Subject to change without notice.